

WHAT IS CLAIMED IS:

1. A video information processing apparatus
associating with a blinking light source, comprising:
an input device configured to input video
5 information;

a memory device configured to store identification
information corresponding to a blinking pattern of the
blinking light source;

10 a blinking light decoder configured to decode the
blinking pattern of the light source blinking in the
video information input by said input device into
corresponding identification information on the basis
of the identification information stored in said memory
device; and

15 an output device configured to output together
with the input video the identification information
converted by said blinking light decoder.

2. An apparatus according to claim 1, wherein
said blinking light decoder includes a recognizing
20 device configured to recognize blinking of said light
source by summing luminance values of all pixels
included in the video information and detecting a
change in sum over several frames.

3. An apparatus according to claim 1, wherein
25 said output device multiplexes the identification
information and the video information while associating
the identification information with the video

0952086 DE 1001
FOOTED 9805360

information, and outputs the multiplexed video.

4. An apparatus according to claim 3, wherein
said output device includes a converter configured to
convert identification information into a sound, and a
5 multiplexer configured to multiplex the sound and video.

5. An apparatus according to claim 1, wherein
said output device represents the identification
information with a character string indicating an
information access point on the Internet.

10 6. A video information processing apparatus
associating with a blinking light source, comprising:
an input device configured to input video
information;

15 a memory device configured to store identification
information corresponding to a blinking pattern of the
blinking light source;

20 a blinking light decoder configured to decode the
blinking pattern of the light source blinking in the
video information input by said input device into
corresponding identification information on the basis
of the identification information stored in said memory
device;

25 a location detector configured to detect a
location of the blinking light source in the video
information; and

an output device configured to output together
with the input video the identification information

09852086-051001

converted by said blinking light decoder and the location of the blinking light source detected by said location detector.

5 7. An apparatus according to claim 6, wherein when the blinking pattern includes explanation information, said output device includes at least one of a display device configured to display the explanation information and an audio device configured to output the explanation information by a sound.

10 8. An apparatus according to claim 6, wherein said blinking light decoder includes a recognizing device configured to recognize blinking of said light source by summing luminance values of all pixels included in the video information and detecting a
15 change in sum over several frames.

9. An apparatus according to claim 6, wherein said output device multiplexes the identification information and the video information while associating the identification information with the video
20 information, and outputs the multiplexed video.

10. An apparatus according to claim 9, wherein said output device includes a converter configured to covert the identification information into a sound and a multiplexer configured to multiples the sound and the
25 video information.

11. An apparatus according to claim 6, wherein said output device represents the identification

0952086-051001

information by a character string indicating an
information access point on the Internet.

12. A video information processing apparatus
associating with a blinking light source, comprising:

5 an input device configured to input video
information;

 a memory device configured to store identification
information corresponding to a blinking pattern of the
blinking light source;

10 blinking light decoder for converting the blinking
pattern of the light source blinking in the video
information input by said input device into
corresponding identification information on the basis
of the identification information stored in said memory
15 device; and

 a video processing device configured to
selectively process the input video in accordance with
the identification information converted by said
blinking light decoder.

20 13. An apparatus according to claim 12, wherein
said processing device masks a video portion specified
by the identification information.

 14. An apparatus according to claim 13, wherein
when the identification information requests no
25 capturing, said processing device smudges the specified
video portion.

 15. An apparatus according to claim 12, wherein

0952036-051001

said blinking light decoder includes means for dividing
a video in a number of video elements arranged in a
matrix pattern, means for calculating a motion vector
at each of the video elements and means for determining
5 as a region to be processed a portion having a motion
vector different from a background.

16. An apparatus according to claim 12, wherein
said blinking light decoder includes a detector
configured to detect as a region to be processed a
10 portion where a hue histogram greatly changes in a
video region expanded from a portion of the blinking
light source.

17. A video information processing apparatus
associating with a blinking light source, comprising:

15 an input device configured to input a video;
a memory device configured to store identification
information corresponding to a blinking pattern of the
blinking light source;

a blinking light decoder configured to decode the
20 blinking pattern of the light source blinking in the
video information input by said input device into
corresponding identification information on the basis
of the identification information stored in said memory
device; and

25 a message output device configured to output a
preset message in accordance with the identification
information converted by said blinking light decoder.

09852086-051001
T0050-9802860

18. A video information processing apparatus associating with a blinking light source, comprising:

an input device configured to input video information;

5 a memory device configured to store identification information corresponding to a blinking pattern of the blinking light source;

10 a blinking light decoder configured to decode the blinking pattern of the light source blinking in the video information input by said input device into corresponding identification information on the basis of the identification information stored in said memory device;

15 a location detector configured to detect a location of the blinking light source in the video information;

a subject memory device configured to store identification information representing a subject to be detected; and

20 a subject detection device configured to detect a location of the subject having the identification information that is converted by said blinking light decoder and stored in said subject memory device, on the basis of the location of the blinking light source
25 detected by said location detector.

19. An apparatus according to claim 18, wherein said subject detection device detects a plurality of

0952086-051001

subjects on the basis of a plurality of pieces of identification information corresponding to a plurality of blinking light sources.

20. An apparatus according to claim 19, wherein
5 said subject detection device includes an output device configured to output a warning when all the subjects corresponding to the plurality of pieces of identification information in the video information cannot be detected.

10 21. A transmitter used in said video information processing apparatus defined in claim 1, comprising:

a blinking pattern memory device configured to store a blinking pattern representing identification information of a subject; and

15 a blinking light source configured to blink and emit light in accordance with the blinking pattern stored in said blinking pattern memory device.

22. A transmitter used for said video information processing apparatus defined in claim 6, comprising:

20 a blinking pattern memory device configured to store a blinking pattern representing identification information of a subject; and

a blinking light source configured to blink and emit light in accordance with the blinking pattern
25 stored in said blinking pattern memory device.

23. A transmitter used for said video information processing apparatus defined in claim 12, comprising:

09352086 "051001

a blinking pattern memory device configured to store a blinking pattern representing identification information of a subject; and

5 a blinking light source configured to blink and emit light in accordance with the blinking pattern stored in said blinking pattern memory device.

24. A transmitter used for said video information processing apparatus defined in claim 17, comprising:

10 a blinking pattern memory device configured to store a blinking pattern representing identification information of a subject; and

a blinking light source configured to blink and emit light in accordance with the blinking pattern stored in said blinking pattern memory device.

15 25. A transmitter used for said video information processing apparatus defined in claim 18, comprising:

a blinking pattern memory device configured to store a blinking pattern representing identification information of a subject; and

20 a blinking light source configured to blink and emit light in accordance with the blinking pattern stored in said blinking pattern memory device.

09352086-051001